

Applicant requests the following Amendments be entered:

IN THE CLAIMS:

1. (Original Claim) A resistance mechanism comprising:
 - a. a base rod, having two ends and a defined axis
 - b. at least one compressible cylinder in a coaxial relation to the base rod.
 - c. a stop structure, abutting the at least one cylinder and disposed at one end of the base rod
 - d. a thrust block, disposed next to the at least one cylinder towards the end opposite the stop structure, the thrust block further comprising:
 - i. a block body having a centrally defined hole, through which the base rod passes; and
 - ii. a pivot axel, extending in a downwards direction from the block body;
 - e. An interface for attaching to a device requiring a resistance feature, the interface located at the end opposite the stop structure;wherein, the resistance mechanism is actuated when the base rod is pulled in a manner to lessen the distance between the thrust block and stop structure, thereby compressing the at least one cylinders and providing resistance.
2. (Original Claim) The resistance mechanism of claim 1 further comprising at least one bushing, coaxially attached inside of each compressible cylinder between the cylinder and the base rod, said bushing being non-compressible so as to limit compression of each cylinder.

3. (Original Claim) The resistance mechanism of claim 1, wherein at least one material from which the at least one compressible cylinder is composed is selected from the group consisting of: rubbers, synthetic rubbers, plastics, polymers, and metals.
4. (Original Claim) The resistance mechanism of claim 3, wherein the stop structure is a handle, coaxially disposed on the base rod.
5. (Original Claim) The resistance mechanism of claim 4, wherein the handle is threadingly engaged to the base rod, allowing for both removal and pre-compression of the at least one cylinder thereby increasing resistance.
6. (Original Claim) The resistance mechanism of claim 2, wherein the stop structure is a handle, coaxially disposed on the base rod.
7. (Original Claim) The resistance mechanism of claim 6, wherein the handle is threadingly engaged to the base rod, allowing for pre-compression of the at least one cylinder thereby increasing resistance.
8. (Original Claim) The resistance device of claim 1, wherein the stop structure is a handle, coaxially disposed on the base rod.
9. (Original Claim) The resistance mechanism of claim 9, wherein the handle is threadingly engaged to the base rod, allowing for pre-compression of the at least one cylinder thereby increasing resistance.
10. (Currently Amended) An exerciser comprising:
 - a. an exerciser base, further comprising:
 - i. a central base support;
 - ii. stabilizing means;
 - iii. a single upwardly extending base vertical axel, extending from the base support;

- b. a rotative body, coaxial with the base-vertical axel and having a generally horizontally displaced axel and a resistance attachment means ~~disposed opposite the horizontally displaced axel;~~
- c. a pair of foot pad arms, cantileverally attached to the horizontally displaced axel, one on either side of the rotative body; and
- d. a pair of ~~attachment rods~~ rod arms, each with a pair of joints disposed at opposite ends of each rod arm and attached individually by a joint to a foot pad arm and both ~~attached~~ interfacing the exerciser base by the other joint to the ~~base axel~~, said location of the connection with the base axel being disposed above the rotative body, thereby locating the connection of the rods with the base axel above the foot pad arms;

wherein foot pad arms are actuated in a vertical manner and thereby draw ~~rods~~ rod arms up and down with foot pad arm and foot pad arms rotate with the rotative body due to the fixed length of the ~~rods~~ rod arms.

- 11. (Original Claim) The exercise device of claim 10 further comprising a resistance means for providing restorative force when the footpad arms are actuated.
- 12. (Original Claim) The exercise device of claim 11, the resistance means comprising:
 - a. a base rod, having two ends and a defined axis
 - b. at least one compressible cylinder in a coaxial relation to the base rod.
 - c. a stop structure, abutting the at least one cylinder and disposed at one end of the base rod
 - d. a thrust block, disposed next to the at least one cylinder towards the end opposite the stop structure, the thrust block further comprising:
 - i. A block body having a centrally defined hole, through which the base rod passes; and

- ii. a pivot axel, extending in a downwards direction from the block body; and
- e. an interface for attaching to a device requiring a resistance feature, the interface located at the end opposite the stop structure;

wherein, the resistance mechanism is actuated when the base rod is pulled in a manner to lessen the distance between the thrust block and stop structure, thereby compressing the at least one cylinders and providing resistance.


13. (Original Claim) The resistance mechanism of claim 12 further comprising at least one bushing, coaxially attached inside of each compressible cylinder between the cylinder and the base rod, said bushing being non-compressible so as to limit compression of each cylinder.
14. (Original Claim) The exercise device of claim 13, wherein at least one material from which the at least one compressible cylinder is composed is selected from the group consisting of: rubbers, synthetic rubbers, plastics, polymers, and metals.
15. (Original Claim) The exercise device of claim 14, wherein the stop structure is a handle, coaxially disposed on the base rod.
16. (Original Claim) The exercise device of claim 15, wherein the handle is threadingly engaged to the base rod, allowing for both removal and pre-compression of the at least one cylinder thereby increasing resistance.
17. (Original Claim) The exercise device of claim 13, wherein the stop structure is a handle, coaxially disposed on the base rod.
18. (Original Claim) The exercise device of claim 17, wherein the handle is threadingly engaged to the base rod, allowing for pre-compression of the at least one cylinder thereby increasing resistance.
19. (Original Claim) The exercise device of claim 12, wherein the stop structure is a handle, coaxially disposed on the base rod.

20. (Original Claim) The exercise device of claim 19, wherein the handle is threadingly engaged to the base rod, allowing for pre-compression of the at least one cylinder thereby increasing resistance.

Applicant submits that Claims 1-20 are now clearly allowable over the prior art and Applicant respectfully requests allowance of these Claims and the case passed for issue. If Examiner believes that a telephonic conference would facilitate the examination of this Application, or would resolve questions Examiner may have, please do not hesitate to call Applicant's Attorney at the contact information below.

Respectfully Submitted,

Date: January 26, 2005



Geoffrey E. Dobbin
Patent Attorney, Reg. # 42,490
4278 South 6220 West
West Valley City, UT 84128-6501
(801) 969-6609
9:00 AM - 4:30PM MST/MDT